

## CLAIMS

1. (currently amended) Circuitry comprising a filter having one or more filter sections, wherein:  
at least one of the one or more filter sections comprises a plurality of transconductor (gm) cells;  
[[and]]  
at least one of the gm cells can itself be configured to have substantially zero transconductance, such that the at least one filter section will oscillate;  
the at least one gm cell has switch circuitry connected to first and second input nodes of the at least one gm cell;  
the at least one gm cell is adapted to be configured to have non-zero transconductance by selectively applying two different input signals to the first and second input nodes using the switch circuitry; and  
the at least one gm cell is adapted to be configured to have substantially zero transconductance by selectively applying a single input signal to the first and second input nodes using the switch circuitry.

2. (original) The invention of claim 1, wherein the at least one filter section is adapted to oscillate at a cutoff frequency of the filter section.

3. (currently amended) The invention of claim 1, wherein the at least one filter section has an input node adapted to receive an input signal for the at least one filter section, an intermediate node, and an output node adapted to present an output signal for the at least one filter section and further comprises:

a first gm cell connected between the input node and the intermediate node;  
a first capacitor connected between the intermediate node and a voltage reference;  
a second gm cell connected between the intermediate node and the output node;  
a second capacitor connected between the output node and the voltage reference;  
a third gm cell connected at both ends to the intermediate node; and  
a fourth gm cell connected between the output node and the intermediate node, wherein:  
the at least one gm cell is the third gm cell; and  
the third gm cell comprises a set of switches that enable the third gm cell to be configured to have substantially zero transconductance, such that the at least one filter section will oscillate.

4. (original) The invention of claim 3, wherein the voltage reference is ground.

5. (original) The invention of claim 1, wherein:  
the at least one filter section is in a main signal path of the filter; and  
the at least one filter section is adapted to be configured to oscillate in order to tune the at least one filter section.

6. (original) The invention of claim 5, wherein each filter section in the main signal path of the filter can be configured to oscillate in order to tune each filter section.

7. (previously presented) The invention of claim 1, wherein:  
the one or more filter sections comprise one or more main-path filter sections and a non-main-path filter section;  
the filter comprises a main signal path having the one or more main-path filter sections;  
the at least one filter section is the non-main-path filter section, which is not part of the main signal path;

7 the non-main-path filter section is a replica of at least one main-path filter section in the main  
8 signal path; and  
9 the non-main-path filter section is adapted to be configured to oscillate in order to tune the at  
10 least one main-path filter section in the main signal path.

1 8. (original) The invention of claim 1, wherein:  
2 the at least one filter section comprises tuning circuitry adapted to tune the at least one filter  
3 section; and  
4 the tuning circuitry is adapted to store tuning control information for the at least one filter section  
5 such that the at least one filter section can be tuned intermittently.

1 9. (previously presented) The invention of claim 8, wherein information based on the  
2 tuning control information of the at least one filter section is used to tune one or more other filter  
3 sections in the filter.

1 10. (original) The invention of claim 1, wherein the at least one filter section is adapted to  
2 oscillate without relying on phase-locked loop circuitry.

1 11. (original) The invention of claim 1, wherein the one or more filter sections are  
2 biquadratic filter sections.

1 12. (original) The invention of claim 1, wherein the one or more filter sections are  
2 connected to form a ladder structure.

1 13. (currently amended) A method for operating a filter having one or more filter sections,  
2 wherein:  
3 at least one of the one or more filter sections comprises a plurality of transconductor (gm) cells;  
4 the method comprising:  
5 applying power to the filter; and  
6 configuring at least one of the gm cells itself to have substantially zero transconductance,  
7 such that the at least one filter section will oscillate;  
8 the at least one gm cell has switch circuitry connected to first and second input nodes of the at  
9 least one gm cell;  
10 the at least one gm cell is adapted to be configured to have non-zero transconductance by  
11 selectively applying two different input signals to the first and second input nodes using the switch  
12 circuitry; and  
13 the at least one gm cell is configured to have substantially zero transconductance by selectively  
14 applying a single input signal to the first and second input nodes using the switch circuitry.

1 14. (original) The invention of claim 13, wherein the at least one filter section oscillates at a  
2 cutoff frequency of the filter section.

1 15. (currently amended) The invention of claim 13, wherein:  
2 the at least one filter section has an input node that receives an input signal for the at least one  
3 filter section, an intermediate node, and an output node that presents an output signal for the at least one  
4 filter section;  
5 the at least one filter section further comprises:  
6 a first gm cell connected between the input node and the intermediate node;  
7 a first capacitor connected between the intermediate node and a voltage reference;  
8 a second gm cell connected between the intermediate node and the output node;

9 a second capacitor connected between the output node and the voltage reference;  
10 a third gm cell connected at both ends to the intermediate node; and  
11 a fourth gm cell connected between the output node and the intermediate node, wherein:  
12 the at least one gm cell is the third gm cell; and  
13 the third gm cell comprises a set of switches that enable the third gm cell to be  
14 configured to have substantially zero transconductance, such that the at least one filter section will  
15 oscillate.

1 16. (original) The invention of claim 13, wherein:  
2 the at least one filter section is in a main signal path of the filter; and  
3 the at least one filter section is configured to oscillate in order to tune the at least one filter  
4 section.

1 17. (previously presented) The invention of claim 13, wherein:  
2 the one or more filter sections comprise one or more main-path filter sections and a non-main-  
3 path filter section;  
4 the filter comprises a main signal path having the one or more main-path filter sections;  
5 the at least one filter section is the non-main-path filter section, which is not part of the main  
6 signal path;  
7 the non-main-path filter section is a replica of at least one main-path filter section in the main  
8 signal path; and  
9 the non-main-path filter section is configured to oscillate in order to tune the at least one main-  
10 path filter section in the main signal path.

1 18. (original) The invention of claim 13, wherein:  
2 the at least one filter section comprises tuning circuitry that tunes the at least one filter section;  
3 and  
4 the tuning circuitry stores tuning control information for the at least one filter section such that  
5 the at least one filter section can be tuned intermittently.

1 19. (original) The invention of claim 18, wherein information about the tuning of the at least  
2 one filter section is used to tune one or more other filter sections in the filter.

1 20. (original) The invention of claim 13, wherein the at least one filter section oscillates  
2 without relying on phase-locked loop circuitry.

1 21. (canceled)

1 22. (currently amended) The invention of claim [[21]] 1, wherein:  
2 the two different input signals are a differential signal pair; and  
3 the single input signal is a common-mode signal corresponding to the differential signal pair.

1 23. (canceled)

1 24. (currently amended) The invention of claim [[23]] 13, wherein:  
2 the two different input signals are a differential signal pair; and  
3 the single input signal is a common-mode signal corresponding to the differential signal pair.

1 25. (new) Circuitry comprising a filter having one or more filter sections, wherein:  
2 at least one of the one or more filter sections comprises a plurality of transconductor (gm) cells;

3 at least one of the gm cells can be configured to have substantially zero transconductance, such  
4 that the at least one filter section will oscillate;  
5 the at least one filter section has an input node adapted to receive an input signal for the at least  
6 one filter section, an intermediate node, and an output node adapted to present an output signal for the at  
7 least one filter section and further comprises:  
8 a first gm cell connected between the input node and the intermediate node;  
9 a first capacitor connected between the intermediate node and a voltage reference;  
10 a second gm cell connected between the intermediate node and the output node;  
11 a second capacitor connected between the output node and the voltage reference;  
12 a third gm cell connected at both ends to the intermediate node; and  
13 a fourth gm cell connected between the output node and the intermediate node, wherein:  
14 the at least one gm cell is the third gm cell; and  
15 the third gm cell comprises a set of switches that enable the third gm cell to be  
16 configured to have substantially zero transconductance, such that the at least one filter section will  
17 oscillate.

1 26. (new) The invention of claim 25, wherein the voltage reference is ground.

1 27. (new) A method for operating a filter having one or more filter sections, wherein:  
2 at least one of the one or more filter sections comprises a plurality of transconductor (gm) cells;  
3 the method comprising:  
4 applying power to the filter; and  
5 configuring at least one of the gm cells to have substantially zero transconductance, such  
6 that the at least one filter section will oscillate;  
7 the at least one filter section has an input node that receives an input signal for the at least one  
8 filter section, an intermediate node, and an output node that presents an output signal for the at least one  
9 filter section; and  
10 the at least one filter section further comprises:  
11 a first gm cell connected between the input node and the intermediate node;  
12 a first capacitor connected between the intermediate node and a voltage reference;  
13 a second gm cell connected between the intermediate node and the output node;  
14 a second capacitor connected between the output node and the voltage reference;  
15 a third gm cell connected at both ends to the intermediate node; and  
16 a fourth gm cell connected between the output node and the intermediate node, wherein:  
17 the at least one gm cell is the third gm cell; and  
18 the third gm cell comprises a set of switches that enable the third gm cell to be  
19 configured to have substantially zero transconductance, such that the at least one filter section will  
20 oscillate.

1 28. (new) A method for operating a filter having one or more filter sections, wherein:  
2 at least one of the one or more filter sections comprises a plurality of transconductor (gm) cells;  
3 the method comprising:  
4 applying power to the filter; and  
5 configuring at least one of the gm cells to have substantially zero transconductance, such  
6 that the at least one filter section will oscillate;  
7 the at least one filter section comprises tuning circuitry that tunes the at least one filter section;  
8 and  
9 the tuning circuitry stores tuning control information for the at least one filter section such that  
10 the at least one filter section can be tuned intermittently.

1           29.     (new) The invention of claim 28, wherein information about the tuning of the at least  
2 one filter section is used to tune one or more other filter sections in the filter.